

KS 260 basic



- Compact, flat shaker with ideal swivel motion, for a maximum shaking weight of 7.5 kg.
- Electronic adjustment of speed and timer
 - LED display for speed and time adjustment
 - Wide range of attachment combinations makes it possible to use almost all shapes and sizes of vessels
 - Attachments are not included, please order separately

Technical Data			
Type of movement [-]	orbital	Orbital diameter [mm]	10
Permissible shaking weight (incl. attachment) [kg]	7.5	Motor rating input [W]	45
Motor rating output [W]	10	Permissible ON time [%]	100
Speed min (adjustable) [1/min]	20	Speed range [1/min]	0 - 500
Speed display [-]	LED line	Timer [-]	yes
Timer display [-]	LED line	Time setting range [min]	5 - 50
Operating mode [-]	timer and continuous operation	Shaking table lock [-]	no
Dimensions (W x H x D) [mm]	360 x 98 x 420	Weight [kg]	8.5
Permissible ambient temperature [°C]	5 - 50	Permissible relative moisture [%]	80
Protection class according to DIN EN 60529 [-]	IP 21	RS 232 interface [-]	yes
Analog output [-]	yes	Voltage [V]	220 - 240 / 100 - 120
Frequency [Hz]	50/60	Power input [W]	45