



A new, attractively designed, test tube shaker.

Designed for mixing small test samples with a touch function.

- Small, compact and reliable

- For small containers up to 30 mm in diameter, e.g. test tubes, centrifuge tubes, Eppendorf beakers

- Fixed speed (2800 rpm)

- Excellent mixing action

- The upper casing and the test tube surface are made from inert plastic. The bottom section is a coated, zinc die-casting

- Includes light 12 V power pack set

- 3-year guarantee on all components

Technical Data			
Type of movement [-]	orbital	Orbital diameter [mm]	4.5
Permissible shaking weight (incl. attachment) [kg]	0.1	Motor rating input [W]	1.2
Motor rating output [W]	0.8	Permissible ON time [%]	100
Speed fix [1/min]	2800	Speed display [-]	none
Timer [-]	no	Timer display [-]	none
Touch function [-]	yes	Shaking table lock [-]	no
Working with microtiter plates [-]	no	Dimensions (W x H x D) [mm]	100 x 70 x 100
Weight [kg]	0.55	Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80	Protection class according to DIN EN 60529 [-]	IP 40
Voltage [V]	100 - 240	Frequency [Hz]	50/60
Power input [W]	30		